

**P-80® Grip-It**  
Quick-Drying Temporary Rubber Assembly Lubricant

Date of issue: April 1, 2020

Replaces version of October 1, 2019

**SECTION 1: Identification**

**1.1 Product identifier**

Trade name **P-80® Grip-It**

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

Relevant identified uses Industrial use  
Do not use for private purposes (household)

**1.3 Details of the supplier of the safety data sheet**

International Products Corporation  
201 Connecticut Drive  
Burlington, NJ  
08016  
United States  
<https://www.ipcol.com/>  
+1 6093868770

**1.3.1 Additional information**

Supplier (distributor)					
Country	Name	Postal code/city	Telephone	e-Mail	Website
United Kingdom	IPCW	SE9 3TL London	+44 (0) 208-857-5678	saleseurope@ipcol.com	www.ipcol.com

e-mail (competent person) **tmcguckin@ipcol.com (Thomas P. McGuckin)**

**1.4 Emergency telephone number**

1.4.1 Emergency information service **1-609-386-8770**  
This number is only available during the following office hours: Mon-Fri 08:00 AM - 04:30 PM, Eastern Time

**SECTION 2: Hazard(s) identification**

**2.1 Classification of the substance or mixture**

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)  
This mixture does not meet the criteria for classification.

**2.2 Label elements**

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)  
- Signal word not required  
- Pictograms not required

**2.3 Other hazards**

There is no additional information.  
Hazards not otherwise classified  
Harmful to aquatic life with long lasting effects (GHS category 3: aquatic toxicity - acute and/or chronic).

**P-80® Grip-It**  
Quick-Drying Temporary Rubber Assembly Lubricant

Date of issue: April 1, 2020

Replaces version of October 1, 2019

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.


**SECTION 3: Composition/information on ingredients**

**3.1 Substances**

Not relevant (mixture)

**3.2 Mixtures**

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
EO PO Isodecyl Alcohol	CAS No 37251-67-5	0.1 - < 1	Skin Irrit. 2 / H315 Eye Dam. 1 / H318 Aquatic Acute 1 / H400 Aquatic Chronic 1 / H410	

**SECTION 4: First-aid measures**

**4.1 Description of first-aid measures**

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

**4.2 Most important symptoms and effects, both acute and delayed**

Symptoms and effects are not known to date.

**4.3 Indication of any immediate medical attention and special treatment needed**

none

**SECTION 5: Fire-fighting measures**

**5.1 Extinguishing media**

Suitable extinguishing media

Water spray, Alcohol resistant foam, BC-powder, Carbon dioxide (CO2)

Unsuitable extinguishing media

Water jet

## P-80® Grip-It

### Quick-Drying Temporary Rubber Assembly Lubricant

Date of issue: April 1, 2020

Replaces version of October 1, 2019

#### 5.2 Special hazards arising from the substance or mixture

#### 5.3 Advice for firefighters

Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

#### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

#### 6.3 Methods and material for containment and cleaning up

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: Sawdust, Kieselgur (diatomite), Sand, Universal binder

Appropriate containment techniques

Use of adsorbent materials.

#### 6.4 Reference to other sections

Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

#### 7.2 Conditions for safe storage, including any incompatibilities

- Specific designs for storage rooms or vessels

- Storage temperature

Recommended storage temperature: 2 – 30 °C

**P-80® Grip-It**  
Quick-Drying Temporary Rubber Assembly Lubricant

Date of issue: April 1, 2020

Replaces version of October 1, 2019

**SECTION 8: Exposure controls/personal protection**

**8.1 Control parameters**

This information is not available.

**8.2 Exposure controls**

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

**SECTION 9: Physical and chemical properties**

**9.1 Information on basic physical and chemical properties**

**Appearance**

Physical state	liquid
Color	colorless-clear
Odor	odorless

**Other safety parameters**

pH (value)	9.8 – 11.3 (25 °C)
Melting point/freezing point	0 °C
Initial boiling point and boiling range	100 °C
Flash point	not determined

**P-80® Grip-It**  
Quick-Drying Temporary Rubber Assembly Lubricant

Date of issue: April 1, 2020

Replaces version of October 1, 2019

Evaporation rate	not determined
Flammability (solid, gas)	not relevant, (fluid)
Explosive limits	not determined
Vapor pressure	not determined
Density	0.995 – 0.999 g/ml at 25 °C
Vapor density	this information is not available

Solubility(ies)

- Water solubility	miscible in any proportion
--------------------	----------------------------

Partition coefficient

- n-octanol/water (log KOW)	this information is not available
-----------------------------	-----------------------------------

Auto-ignition temperature	not determined
---------------------------	----------------

Viscosity

- Kinematic viscosity	10.01 mm <sup>2</sup> /s
-----------------------	--------------------------

- Dynamic viscosity	10 cP
---------------------	-------

Explosive properties	none
----------------------	------

Oxidizing properties	none
----------------------	------

**SECTION 10: Stability and reactivity**

**10.1 Reactivity**

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

**10.2 Chemical stability**

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure. Shelf-life: Two years from the date of manufacture.

**10.3 Possibility of hazardous reactions**

No known hazardous reactions.

**10.4 Conditions to avoid**

Do not mix with other chemicals.

**10.5 Incompatible materials**

Avoid extended contact with uncured paint, zinc, aluminum, cold rolled steel, or copper and its alloys. Avoid contact with polycarbonate, polymethyl methacrylate, and polyphenylene oxide as these plastics may craze over time. Refer to product's compatibility sheets for further details.

## **P-80® Grip-It**

### Quick-Drying Temporary Rubber Assembly Lubricant

Date of issue: April 1, 2020

Replaces version of October 1, 2019

#### **10.6 Hazardous decomposition products**

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

### **SECTION 11: Toxicological information**

#### **11.1 Information on toxicological effects**

Basis of test data.

##### Classification procedure

The classification is based on tested mixture.

##### **Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)**

This mixture does not meet the criteria for classification.

##### Acute toxicity

Shall not be classified as acutely toxic.

##### Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

##### Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

##### Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

##### Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

##### Carcinogenicity

Shall not be classified as carcinogenic.

##### Reproductive toxicity

Shall not be classified as a reproductive toxicant.

##### Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

##### Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

##### Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

### **SECTION 12: Ecological information**

#### **12.1 Toxicity**

Harmful to aquatic life with long lasting effects.

##### Biodegradation

Not readily biodegradable.

## P-80® Grip-It

### Quick-Drying Temporary Rubber Assembly Lubricant

Date of issue: April 1, 2020

Replaces version of October 1, 2019

#### 12.2 Persistence and degradability

Data are not available.

#### 12.3 Bioaccumulative potential

Data are not available.

#### 12.4 Mobility in soil

Data are not available.

#### 12.5 Results of PBT and vPvB assessment

Data are not available.

#### 12.6 Other adverse effects

Endocrine disrupting potential

None of the ingredients are listed.

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Sewage disposal-relevant information

May be disposed according to local, state and federal regulations.

Waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

#### Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

### SECTION 14: Transport information

14.1 UN number	not subject to transport regulations
14.2 UN proper shipping name	not assigned
14.3 Transport hazard class(es)	not assigned
14.4 Packing group	not assigned
14.5 Environmental hazards	non-environmentally hazardous acc. to the dangerous goods regulations
14.6 Special precautions for user	
There is no additional information.	

**P-80® Grip-It**  
Quick-Drying Temporary Rubber Assembly Lubricant

Date of issue: April 1, 2020

Replaces version of October 1, 2019

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations specific for the product in question**

**National regulations (United States)**

**Toxic Substance Control Act (TSCA)** all ingredients are listed

**Superfund Amendment and Reauthorization Act (SARA TITLE III )**

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

None of the ingredients are listed.

- Specific Toxic Chemical Listings (EPCRA Section 313)

None of the ingredients are listed

**Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)**

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

None of the ingredients are listed.

**Clean Air Act**

None of the ingredients are listed.

**Right to Know Hazardous Substance List**

- Hazardous Substance List (NJ-RTK)

none of the ingredients are listed

**Industry or sector specific available guidance(s)**

**NPCA-HMIS® III**

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	/	none
Health	0	no significant risk to health
Flammability	0	material that will not burn under typical fire conditions
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

**NFPA® 704**

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	0	material that will not burn under typical fire conditions
Health	0	material that, under emergency conditions, would offer no hazard beyond that of ordinary combustible material
Instability	0	material that is normally stable, even under fire conditions



**P-80® Grip-It**  
Quick-Drying Temporary Rubber Assembly Lubricant

Date of issue: April 1, 2020

Replaces version of October 1, 2019

Category	Degree of hazard	Description
Special hazard		

**National inventories**

Country	National inventories	Status
EU	REACH Reg.	not all ingredients are listed
US	TSCA	all ingredients are listed

**Legend**

REACH Reg. REACH registered substances  
TSCA Toxic Substance Control Act

**15.2 Chemical Safety Assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information, including date of preparation or last revision**

**Abbreviations and acronyms**

Abbr.	Descriptions of used abbreviations
49 CFR US DOT	49 CFR U.S. Department of Transportation
Aquatic Acute	Hazardous to the aquatic environment - acute hazard
Aquatic Chronic	Hazardous to the aquatic environment - chronic hazard
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
DGR	Dangerous Goods Regulations (see IATA/DGR)
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
IMDG	International Maritime Dangerous Goods Code
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
vPvB	Very Persistent and very Bioaccumulative

## **P-80® Grip-It**

### Quick-Drying Temporary Rubber Assembly Lubricant

Date of issue: April 1, 2020

Replaces version of October 1, 2019

**Key literature references and sources for data**

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

**Classification procedure**

The classification is based on tested mixture.

**List of relevant phrases (code and full text as stated in chapter 2 and 3)**

Code	Text
H315	Causes skin irritation.
H318	Causes serious eye damage.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

**Disclaimer**

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.