

P-80® RediLube
Temporary Rubber Assembly Lubricant

Date of issue: January 1, 2021

Replaces version of April 1, 2020

SECTION 1: Identification**1.1 Product identifier**Trade name **P-80® RediLube****1.2 Relevant identified uses of the substance or mixture and uses advised against**Relevant identified uses Industrial use
Do not use for private purposes (household)**1.3 Details of the supplier of the safety data sheet**International Products Corporation
201 Connecticut Drive
Burlington, NJ
08016
United States
<https://www.ipcol.com/>
+1 6093868770
e-Mail (competent person) tmcguckin@ipcol.com**1.3.1 Additional information**

Manufacturer						
Name	Street	Postal code/city	Country	Telephone	e-Mail	Website
International Products Corporation	201 Connecticut Drive	08016 Burlington	United States	1-609-386-8770	mkt@Ipcol.com	www.ipcol.com

1.4 Emergency telephone number1.4.1 Emergency information service 1-609-386-8770
This number is only available during the following office hours: Mon-Fri 08:00 AM - 04:30 PM, Eastern Time**SECTION 2: Hazard(s) identification****2.1 Classification of the substance or mixture**Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)
This mixture does not meet the criteria for classification.**2.2 Label elements**Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)
not required

P-80® RediLube

Temporary Rubber Assembly Lubricant

Date of issue: January 1, 2021

Replaces version of April 1, 2020

2.3 Other hazards

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.





SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
Fatty acids, compds. with tri-ethanolamine	CAS No 2717-15-9	1 – < 5	Skin Irrit. 2 / H315 Eye Irrit. 2 / H319	
2-methylisothiazol-3(2H)-one	CAS No 2682-20-4	0 – < 0.1	Acute Tox. 3 / H301 Acute Tox. 3 / H311 Acute Tox. 2 / H330 Skin Corr. 1B / H314 Eye Dam. 1 / H318 Skin Sens. 1A / H317 Aquatic Acute 1 / H400 Aquatic Chronic 2 / H411	  

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

P-80® RediLube
Temporary Rubber Assembly Lubricant

Date of issue: January 1, 2021

Replaces version of April 1, 2020

SECTION 5: Fire-fighting measures**5.1 Extinguishing media**

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO₂)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Nitrogen oxides (NO_x)**5.3 Advice for firefighters**

Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: Sawdust, Kieselgur (diatomite), Sand, Universal binder

Appropriate containment techniques

Use of adsorbent materials.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

P-80® RediLube

Temporary Rubber Assembly Lubricant

Date of issue: January 1, 2021

Replaces version of April 1, 2020

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

- Specific designs for storage rooms or vessels

- Storage temperature

Recommended storage temperature: 2 – 30 °C

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

This information is not available.

Relevant DNELs of components of the mixture

Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
2-methylisothiazol-3(2H)-one	2682-20-4	DNEL	0.021 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
2-methylisothiazol-3(2H)-one	2682-20-4	DNEL	0.043 mg/m ³	human, inhalatory	worker (industry)	acute - local effects

Relevant PNECs of components of the mixture

Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
2-methylisothiazol-3(2H)-one	2682-20-4	PNEC	3.39 µg/l	aquatic organisms	freshwater	short-term (single instance)
2-methylisothiazol-3(2H)-one	2682-20-4	PNEC	3.39 µg/l	aquatic organisms	marine water	short-term (single instance)
2-methylisothiazol-3(2H)-one	2682-20-4	PNEC	0.23 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
2-methylisothiazol-3(2H)-one	2682-20-4	PNEC	0.047 mg/kg	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

P-80® RediLube
Temporary Rubber Assembly Lubricant

Date of issue: January 1, 2021

Replaces version of April 1, 2020

Skin protection**- Hand protection**

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties****Appearance**

Physical state	liquid
Color	cloudy-white
Odor	characteristic

Other safety parameters

pH (value)	7.5 - 9.0
Melting point/freezing point	not determined
Initial boiling point and boiling range	100 °C
Flash point	not determined
Evaporation rate	not determined
Flammability (solid, gas)	not relevant, (fluid)
Explosive limits	not determined
Vapor pressure	not determined
Density	0.998 g/ml at 25 °C
Vapor density	this information is not available
Solubility(ies)	not determined

P-80® RediLube
Temporary Rubber Assembly Lubricant

Date of issue: January 1, 2021

Replaces version of April 1, 2020

Partition coefficient

- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	not determined

Viscosity

- Kinematic viscosity	40.08 mm ² /s at 25 °C
- Dynamic viscosity	10 – 40 cP at 25 °C
Explosive properties	none
Oxidizing properties	none

SECTION 10: Stability and reactivity**10.1 Reactivity**

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure. Shelf-life: Two years from the date of manufacture.

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Do not mix with other chemicals.

10.5 Incompatible materials

Avoid extended contact with uncured paint, zinc, aluminum, cold rolled steel, or copper and its alloys. Avoid contact with polycarbonate, polymethyl methacrylate, and polyphenylene oxide as these plastics may craze over time. Refer to product's compatibility sheets for further details.

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information**11.1 Information on toxicological effects**

Basis of test data.

Classification procedure

The classification is based on tested mixture.

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

This mixture does not meet the criteria for classification.

P-80® RediLube
Temporary Rubber Assembly Lubricant

Date of issue: January 1, 2021

Replaces version of April 1, 2020

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components of the mixture

Name of substance	CAS No	Exposure route	ATE
2-methylisothiazol-3(2H)-one	2682-20-4	oral	120 mg/kg
2-methylisothiazol-3(2H)-one	2682-20-4	dermal	242 mg/kg
2-methylisothiazol-3(2H)-one	2682-20-4	inhalation: dust/mist	0.11 mg/l/4h

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information**12.1 Toxicity**

Shall not be classified as hazardous to the aquatic environment.

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

P-80® RediLube
Temporary Rubber Assembly Lubricant

Date of issue: January 1, 2021

Replaces version of April 1, 2020

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Other adverse effects

Endocrine disrupting potential

None of the ingredients are listed.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Sewage disposal-relevant information

May be disposed according to local, state and federal regulations.

Waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number	not subject to transport regulations
14.2 UN proper shipping name	not assigned
14.3 Transport hazard class(es)	not assigned
14.4 Packing group	not assigned
14.5 Environmental hazards	non-environmentally hazardous acc. to the dangerous goods regulations
14.6 Special precautions for user	
There is no additional information.	

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations specific for the product in question****National regulations (United States)****Toxic Substance Control Act (TSCA)** all ingredients are listed**Superfund Amendment and Reauthorization Act (SARA TITLE III)**

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

None of the ingredients are listed.

- Specific Toxic Chemical Listings (EPCRA Section 313)

None of the ingredients are listed

P-80® RediLube

Temporary Rubber Assembly Lubricant

Date of issue: January 1, 2021

Replaces version of April 1, 2020

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)
None of the ingredients are listed.

Clean Air Act

None of the ingredients are listed.

Right to Know Hazardous Substance List

- Hazardous Substance List (NJ-RTK)
none of the ingredients are listed

National inventories

Country	National inventories	Status
EU	REACH Reg.	not all ingredients are listed
US	TSCA	all ingredients are listed

Legend

REACH Reg. REACH registered substances
TSCA Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
49 CFR US DOT	49 CFR U.S. Department of Transportation
Acute Tox.	Acute toxicity
Aquatic Acute	Hazardous to the aquatic environment - acute hazard
Aquatic Chronic	Hazardous to the aquatic environment - chronic hazard
ATE	Acute Toxicity Estimate
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
IMDG	International Maritime Dangerous Goods Code

P-80® RediLube

Temporary Rubber Assembly Lubricant

Date of issue: January 1, 2021

Replaces version of April 1, 2020

Abbr.	Descriptions of used abbreviations
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
Skin Sens.	Skin sensitization
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

The classification is based on tested mixture.

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.